

AUDIO AND VIDEO QUALITY CHECKLIST FOR LRPA PRODUCERS

AUDIO

Prior to recording on the JVC, LRPA recommends a final check of your audio. To do this, look at the mic settings, located on the *top left* of the JVC. **AUDIO SETTINGS SHOULD ALWAYS BE IN AUTO MODE.**Consult photo # 1 below.

- Under CH-2 INPUT, the setting should always be set at INPUT 1
- Under AUDIO INPUT, the setting should always be set at MIC + 48V on BOTH lines
- Both AUDIO SELECT settings (top and bottom) should be set left to AUTO
- Please do not adjust the audio levels (the small wheels to the right of "AUDIO SELECT")

If these settings have moved, make sure to re-set them as noted above.

Perform a quick audio check by snapping your fingers or speaking near the onboard mic.

YOU SHOULD SEE ALWAYS SEE AUDIO LEVELS ON YOUR PREVIEW MONITOR.



Photo #1: Mic Settings Photo #2: ND Filter

VIDEO

Prior to recording on the JVC, LRPA recommends a final check of your video quality. To do this, look at the ND FILTER setting, located on the *left side of the JVC between the lens and the preview monitor*. **THE ND FILTER SHOULD ALWAYS BE SET TO OFF (the lowest setting).** Consult photo # 2 above. If this setting has moved, make sure to re-set it to the lowest setting as noted above.